## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

30urces						
Supplier's name	e or trade mark:	Clas Ohlson				
Supplier's address: -						
Model identifie	r: 368208000 (N	IK-020011001802)				
Type of light so	urce:					
Lighting technol	logy used:	LED	Non-directional or directional:	NDLS		
Light source cap-type		E27				
(or other electri	ic interface)					
Mains or non-mains:		MLS	Connected light source (CLS):	Yes		
Colour-tuneable light source:		Yes	Envelope:	-		
High luminance	light source:	No				
Anti-glare shield	d:	Yes	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		9	Energy efficiency class	F		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power (P <sub>on</sub> ), expressed in W		9,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,40		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		0,40	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	120	Spectral power	See image		
dimensions	Width	60	distribution in the	in last page		
without	Depth	60				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	9			
		Chromaticity	0,317			
		coordinates (x and y)	0,341			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	21	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	Yes <sup>(b)</sup>	If yes then replacement claim (W)	60			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;