Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Sources . | | | | | | |
|--|------------------|-------------------------|--|--------------|--|--|
| Supplier's name | e or trade mark: | North Light | | | | |
| Supplier's address: - | | | | | | |
| Model identifie | r: 367539000 (K- | -MWL-RN5W) | | | | |
| Type of light so | urce: | | | | | |
| Lighting technol | logy used: | LED | Non-directional or directional: | NDLS | | |
| Light source cap-type | | 230V | | | | |
| (or other electri | ic interface) | | | | | |
| Mains or non-m | nains: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable | e light source: | No | Envelope: | - | | |
| High luminance | light source: | Yes | | | | |
| Anti-glare shield | d: | Yes | Dimmable: | No | | |
| Product parameters | | | | | | |
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 5 | Energy efficiency class | F | | |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 160 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 | | |
| On-mode power (P _{on}), expressed in W | | 5,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,50 | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 | | |
| Outer | Height | 300 | Spectral power | See image | | |
| dimensions | Width | 300 | distribution in the | in last page | | |
| without | Depth | 79 | | | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | | | | |
|--|------|---|-------|--|--|--|
| Claim of equivalent power ^(a) | Yes | If yes, equivalent power (W) | 15 | | | |
| | | Chromaticity | 0,470 | | | |
| | | coordinates (x and y) | 0,415 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 2 | Survival factor | 0,90 | | | |
| the lumen maintenance factor | 0,96 | | | | | |

(a)'-': not applicable; (b)'-': not applicable;